



Self Bunded (Double Wall)

# LIQUITAINER CONTAINERISED **TANKS**

Suitable for the Storage and Dispensing of Diesel, Lubricants, Kerosene and Petrol.









#### **FEATURES:**


- Integrated Bunded Pump Bay and Tank Access Platform design providing access to the full tank functionality in one convenient location on the tank.
- Unique rounded rectagular tank profile maximises the storage capacity of the tank and provides the strength of a cylindrical design.
- Rounded roof profile that will not pool water / snow or sand.
- CSC plated as 10ft / 20ft / 40ft / 48ft Standard Container.
- Dispensing Equipment housed within a lockable bunded pump bay housing.
- Lockable Container Doors with option for Roller
- Supplied with Interstitial Emergency Relief Vent that will relieve the gap between the two tanks in the event of a fire.
- DN80 Fill Point c/w Camlock Male Fitting / Dust Cap / Fire Safe Full Bore Ball Valve / Wafer Style Non Return Valve.
- DN80 Suction Outlet c/w Anti Syphon Valve and Two Piece Full Bore Fire Safe Ball Valve.

- DN80 Mechanical Overfill Valve + 12V Battery Operated Overfill Alarm.
- 2 x 600mm manways with integrated tank access ladder assembly.
- Fold out AS1657 designed and approved access ladder.
- Removable plate to allow the linking of multiple tanks in tank farm applications.
- Full under tank visibility allows for regular visual inspect of the tank base and prevents the base rusting by providing for unrestricted air flow under the tank.
- Paint Colour RAL9003 Signal White/Tanks are sandblasted to SA2 Standard. Hempel Marine Paint 3 Stage process. Primer Hempadur 1530. 2nd Coat Hempadur Hi-Build 4520. Final Coat Hempathane Enamel 55100 Finished dry film thickness no less than 180 um.
- Supplied with all required statutory safety decals for your region of operation.





PRODUCT RANGE:								
Code	Capacity	Safe Fill Level	<b>Length</b> (mm)	<b>Width</b> (mm)	<b>Height</b> (mm)	<b>Weight</b> (kg)	Container Footprint	Integrated Pump Bay
LT12	12,000L	10,100L	3,000	2,438	2,896	4,500	10FT High Cube	Yes
LT16	16,000L	15,000L	3,000	2,438	2,896	4,500	10FT High Cube	No
LT30	30,000L	26,500L	6,058	2,438	2,896	7,500	20FT High Cube	Yes
LT38	38,000L	33,500L	6,058	2,438	2,896	7,500	20FT High Cube	No
LT65	65,000L	62,300L	12,192	2,438	2,896	14,500	40FT High Cube	Yes
LT75	75,000L	69,000L	12,192	2,438	2,896	14,500	40FT High Cube	No









**Liquitainer being used for Generators** 



Liquitainer Integrated Self Bunded Pump Bay





## **CERTIFICATIONS**



Certificate of Compliance #20120912-MH49221 for UL 142, ULC-S601.



Decals manufactured to comply with AS1319 and AS2700.

### **PETRO Contact Information**

#### **AFRICA**

#### **South Africa**

Factory 14 Bentonite Street Alrode, Alberton, Johannesburg South Africa P: +27 (0)11 864 7758 F: +27 (0) 11 864 1649 E: sales@petroindustrial.co.za

#### UAE

#### **Dubai**

Office LB17330, Lobby Building 17 Jebel Ali Free Zone PO Box 18602 Dubai, United Arab Emirates P: +971 488 76688 F: +971 488 76932 E: salesuae@petroind.com

#### **AUSTRALIA**

#### **Eastern Australia**

Factory 2, 106 Potassium Street PO Box 407 Narangba QLD 4504 P: 07 3204 9558 F: 07 3293 4852 E: sales@petroindustrial.com.au

#### **Western Australia**

173 Mulgul Road, Malaga WA 6090 AU P: +61 (8) 6305 0855 E: saleswa@petroperth.com.au



petroind.com